Clipper® Hook Selection Chart

Minimum Pulley Diameter	Wire Diameter	Connecting Pin	Belt Thickness											
			1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm
24mm	0.6	1.7	25											
	0.6	1.7	UCM36SLXSP											
	0.9 x 0.7	1.7		UCM36SLSP										
51mm	0.9 x 0.7	1.7	UCM36XSP											
	0.8	1.7	30											
	0.9 x 0.7	1.7		UCM36SP										
	0.9 x 0.7	1.7		36SP										
	1	1.7		1XSP										
	1	1.7		UX1SP										
	0.9 x 0.7	1.7			UCM36									
	0.9 x 0.7	1.7			36									
	1	1.7			1SP									
	1	1.7				1								
	1	1.7				UX1								
	1.4	2.4				U2SP								
	1.4	2.4				U2								
76mm	1.4	2.4				2SP								
	1.4	2.4					2							
89 mm	1.4	2.4						3						
	1.4	2.4						U3						
102mm	1.4	2.8							4					
	1.4	3.2								4 1/2				
127mm	1.4	2.8							U4					
	1.4	3.2									5			
	1.4	3.2									U5			
152mm	1.4	4.0										6		
	1.4	4.0										U6		
175mm	1.4	4.0											7	
	1.4	4.0											U7	

Carded **Unibar®**

Fastener Material Characteristics

Metal	Abrasion Resistance	Chemical Resistance	Rust Resistance	Available Hook Sizes
Galvanized	Good	Poor	Good	25, 1, 2-7
Coated Steel	Good	Poor	Poor	U2-U7
High Tensile Steel	Good to Excellent	Fair	Good	1, 2-7
Rectangular High Tensile Steel	Good to Excellent	Fair	Good	4-1/2
430 Stainless Steel	Good	Fair to Good	Good	1, 2-7, UX1, U2-U7
316L Stainless Steel	Good	Good to Excellent	Excellent	All

FLEXIBLE STEEL LACING COMPANY ISO 9000 REGISTERED

Flexible Steel Lacing Company
2525 Wisconsin Avenue
Downers Grove, IL 60515-4200 U.S.A.
Telephone: (630)-971-0150
Fax: (630)-971-1180
E-mail: advertising@flexco.com
Visit our Web site at: www.flexco.com

FLEXCO

Australia: 61-2-9680-3322 • England: 44-1457-891000 • Germany: 49-7428-9406-0
Mexico: 52 55 56-74-53-26 • New Zealand: 64-9-415-4488 • Republic of South Africa: 27-11-974-2771

©2002 Flexible Steel Lacing Company 7/02 Part #X1183
Clipper® and Unibar® are registered trademarks of Flexible Steel Lacing Company.